

# Morpho Access MAJ Series

## Technical Specifications



Manage your biometric terminals with the world's leading solutions based software. BioManager is specifically designed to get peak performance from Morpho Access Terminals.

- **Database**
- 500 enrolled personnel (two fingers per person) or 3,000 enrolled personnel (two fingers per person) with license
- Stores up to 8,000 logs of activity in off-line mode.
- **Matching**
- 0.6s in 1:1 authentication (J-Dual)
- 0.8s in 1:500 identification
- **Interfaces**
- Ethernet wired, on RJ45 or Wireless (option)
- Customizable Wiegand
- Relay
- **Morpho Access Unit**
- Contactless Card Reader (J-Dual)
- MIFARE® (1K, 4K) and DESFire® (2K, 4K, 8K)
- Optical Sensor: 0.6" (14mm) x 0.9" (22 mm) 500 dpi, 256 grey levels
- Multi-color LED, Multi-tone Buzzer
- **Security**
- Secure screws, anti-tamper & anti-pulling switches
- **Physical characteristics**
- Height 5" (127mm) x Width 3.15" (80mm) x Depth 2.4" (61.5mm)
- Weight: 0.4 lb (0.19kg)
- **Voltage supply**
- External 9V to 16V (250mA typical @12V) or Power Over Ethernet
- **Operating Conditions**
- Operating temperature range: 14°F to 122°F (-10°C to 50°C)
- Operating humidity range: 10% to 80%
- IP65 (once wall-mounted)



**America** 1.888.444.8620  
**Australia** 1300.765.229  
**Africa** +27.11.083.7499

Approved Dealer:

**Identityone**™ 

[www.identityone.net](http://www.identityone.net)  
[sales@identityone.net](mailto:sales@identityone.net)