

# MorphoAccess MA-VPBio

## Technical Specifications



Manage your biometric terminals with the world's leading solutions based software. BioManager is specifically designed to get peak performance from MorphoAccess Terminals.

- **Database**
- 5,000 users on standard version
- Upgradable to 10,000 users with license
- **Matching**
- One-to-one authentication in 1s (average)
- One-to-many identification in 1s average (1 to 500), 1.5s average (1 to 5,000)
- **Interfaces**
- Ethernet wired, on RJ45 or Wireless (option)
- Customizable Wiegand
- Relay
- **MorphoAccess Unit**
- Optical Sensor
- Dual ARM9 CPU
- Intuitive MMI with positioning guides, finger presence detection, multicolor LED indicator and multi-tone buzzer
- **Security**
- Secure screws, anti-tamper & anti-pulling switches
- SSL on TCP/IP
- **Physical characteristics**
- Height 6.3" (160mm) x Width 3.54" (90mm) x Depth 4.92" (125mm)
- Weight: 1.1 lbs (0.515kg)
- **Voltage supply**
- External 9V to 16V (1A minimum @12V) or Power Over Ethernet
- **Operating Conditions**
- Operating temperature range: 14°F to 122°F (-10°C to 50°C)
- Operating humidity range: 10% to 80% (non condensing)
- IP65 (once wall-mounted)



**America** 1.888.444.8620  
**Australia** 1300.765.229  
**Africa** +27.11.083.7499

Approved Dealer:

**Identityone**™ 

[www.identityone.net](http://www.identityone.net)  
[sales@identityone.net](mailto:sales@identityone.net)